

Dräger Alcotest® 5820 Alcohol Screening Device

The Dräger Alcotest® 5820 allows the professional user to perform a breath alcohol test with speed and precision. The measuring technology of this small and user-friendly portable measuring device has already been proven in over 200,000 units in use worldwide.



USA: For Law Enforcement Purposes Only

Benefits

Breath alcohol testing made easy

The device is ready to use within seconds. This means that you can perform an (active) test on a subject at any time. It is also possible to measure alcohol in the ambient air (passive), in which case a mouthpiece isn't required.

All functions required for a measurement are activated with the convenient green OK button, while two menu buttons are used for navigation.

Versatile and tough

The tried and tested electro-chemical Dräger sensor in the Alcotest 5820 is distinguished by its very fast response times and a long service life. It operates with extreme precision and reliability. The analysis is reliable even at temperatures of -5 to +50 °C / 23 to 122 °F. The sensor also delivers reliable results quickly in case of a high alcohol content, for both active and passive measurements.

Convenient to use

Dealing with intoxicated people requires a high degree of attention and concentration. An intuative operation of the device is an important aspect for ease of use and smooth breath testing procedures.

All measurement functions can be operated with just one button to make it easier for you to perform the test. The large back-lit display is easy to understand due to its full-text messages which guide you securely through the alcohol test. An LED and audible signal complement the display and indicate the end of a measurement process. Two menu buttons are used to navigate through the menu, enabling you to perform functions such as reviewing the last test results.

Simply hygienic: the Slide'n'click mouthpiece

The sophisticated product design meets the requirements for performing the breath alcohol test quickly, easily and hygienically: The shape of the Slide'n'click mouthpiece allows you to intuitively fit it correctly, even in the dark. The Alcotest 5820 is ready to use again immediately after changing the mouthpiece. Furthermore, attempts at obstruction are consistently rejected by the device: The air outlet cannot be closed, foiling any attempts to manipulate the device when giving a breath sample.

A spacer on the mouthpiece keeps the lips of the person being tested from coming into contact with the device's housing. The spacer can also be used as a mouthpiece ejector if necessary. Mouthpieces with return valve are also available upon request.

Accessories



Mouthpieces (slide'n'click)

Available in packs of 100, 250, and 1000 mouthpieces with or without non-return valve.



Protective cover

The cover offers additional protection. Meaning, it can be operated while in the cover, since the display is visible at all times.

Related Products



Dräger Alcotest® 6820

Keeping the roads safe and free of impaired drivers is an unpredictable and high stress job. Dräger designed the Alcotest® 6820 handheld breathalyzer specifically for the needs of law enforcement officers. It's easy to use and provides fast, reliable results in the toughest environments you face when every second matters.

Related Products



Dräger Alcotest® 9510

The Dräger Alcotest® 9510 is an advanced breath alcohol measuring instrument for evidential applications. It is designed to comply with national and international requirements and regulations (OIML R 126). With dual sensor technology, intuitive color touch screen interface, and modern design the Alcotest® 9510 sets superior standards.



Dräger DrugCheck® 3000

Use the Dräger DrugCheck® 3000 to find out within minutes if a person recently consumed certain drugs. The compact and quick oral fluid based drug test yields reliable results affordably and easily. The device does not require electricity and can be used anywhere.



Dräger DrugTest® 5000

No pipetting, no drips, no timing: Collecting an oral fluid sample is quick and easy with the Dräger DrugTest® 5000. The collected sample can then be analysed immediately for accurate results on the spot.

Technical Data

| Measuring principle | Electrochemical DrägerSensor in 1/4" technology; alcohol specific |
|--------------------------------|---|
| Measuring range | 0 to 2.5 mg/L; if measurement range limit is exceeded, a message is displayed |
| Sampling | Standard: automatic sampling when minimum volume resp. |
| | defined blow time is reached; |
| | Passive sampling without mouthpiece or manual initiation |
| | of sampling possible |
| Ready for use | Approx. 2 s after switching on |
| Display of measurement result | After approx. 3 s (at 0 mg/L); |
| | after approx. 10 s (at 0.5 mg/L, room temperature) |
| Operating temperature | -5 to +50 °C / 23 to 122 °F |
| Relative humidity | 10 to 100 % relative humidity (non-condensing and in operating state) |
| Ambient pressure | 600 to 1,300 hPa / 17.7 to 38.4 inch Hg |
| Display | Graphic backlit LCD display; |
| | 32 x 22 mm / 1.3" x 0.9" (128 x 64 pixels) |
| LED | 2-colour, to support display of results and warning messages |
| Audible signal | Different signal tones to support display messages and warnings |
| Datalogger | Storage of last 100 tests with test numbers |
| Power supply | 1 x CR123A-Battery, charge level indicator in display, |
| | with one battery approx. 1,500 breath tests can be done. |
| Mouthpiece adaption | Improved Slide'n'click mouthpiece attachment; can be fitted for |
| | right or left orientation |
| Mouthpiece | Hygienically, individually packaged, with tamper-proof, tamper- |
| | proof air outlet, mouthpiece ejector and spacer between mouth |
| | and instrument housing |
| Operating concept | Measurement functions can be performed using just one button; |
| | menu navigation is via two menu button |
| Calibration | Wet gas or dry gas calibration |
| Housing | Impact resistant ABS/PC |
| Dimensions (W x H x D), weight | Approx. 50/60 x 141 x 31 mm / 2"/2.4" x 5.6" x 1.2"; approx. 150 |
| | g / 0.33 lbs, incl. battery |
| Instrument configuration | Direct menu-guided configuration of instrument settings |
| | (PIN required) No additional PC software needed |
| Vibration and shock | EN 60068-2-27, EN 60068-2-6; EN 60068-2-64 |
| CE marking | 2014/30/EU (electromagnetic compatibility) |
| Norm | EN 15964, NHTSA, FDA Conformity, depending on configuration |
| Internal clock | Warning or deactivation after end of service interval |
| Protection type | IP54 |

Ordering Information

| Dräger Alcotest® 5820 – Configurator | 83 24 921 |
|---|-----------|
| Dräger Alcotest® 5820 – fixed configuration | 83 25 200 |
| (device, 3 mouthpieces, 1 battery, hand loop, plastic | |
| transportation case. | |
| Dräger Alcotest® 5820 – USA | 83 24 940 |
| Dräger Alcotest® 5820 – Japan | 83 25 230 |
| Mouthpiece - Package with 100 pieces | 68 10 690 |
| Mouthpiece - Package with 250 pieces | 68 10 825 |
| Mouthpiece - Package with 1,000 pieces | 68 10 830 |

Ordering Information

| Mouthpiece with non return valve - Package with 100 pieces | 68 11 055 |
|--|-----------|
| Mouthpiece with non return valve - Package with 250 pieces | 68 11 060 |
| Mouthpiece with non return valve - Package with 1,000 pieces | 68 11 065 |
| Protection bag, black | 83 24 999 |
| Battery | 45 43 808 |
| | |

Notes

Notes

91 01 018 | 16.12-2 | HQ | PP | Subject to modifications | © 2016 Drägerwerk AG & Co. KGaA

Not all products, features, or services are for sale in all countries. Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS Drägerwerk AG & Co. KGaA Moislinger Allee 53–55

Moislinger Allee 53–55 23558 Lübeck, Germany www.draeger.com

AUSTRALIA

MELBOURNE (HEAD OFFICE)

Draeger Safety Pacific Pty. Ltd.
8 Acacia Place
Notting Hill VIC 3168
Tel (Local Toll-free) 1800 372 437 Tel
+61 3 9265 5000
Fax (Local Toll-free) 1800 647 484
Fax +61 3 9265 5095

SALES AND SERVICE CENTRES ADELAIDE

customer.service@draeger.com

258 Grange Road Flinders Park SA 5025

BRISBANE

Unit 7 Rocklea Place 1909 Ipswich Rd Rocklea QLD 4106

DARWIN

Unit 2/101 Koonawarra Rd Winnellie NT 0820

GLADSTONE

Unit 5, 39 Toolooa St Gladstone QLD 4680

KALGOORLIE

184 Hay Street Kalgoorlie WA 6430

KARRATHA

Unit 1, 16 Hedland Place Karratha WA 6714

PERTH

72A Irvine Drive Malaga WA 6090

SYDNEY

24/7 Salisbury Rd Castle Hill NSW 2155

NEW ZEALAND

AUCKLAND

Unit 4, 24 Bishop Dunn Place East Tamaki, Auckland Tel 0800 372 437 Fax 0800 733 133

WELLINGTON

Unit 3, Parkhead Court 33 Pito-One Road Korokoro, Lower Hutt 5012

Locate your Regional Sales Representative at: www.draeger.com/contact

